



TIMING BELT PULLEY AT10MM PITCH (TRAPEZOIDAL TEETH)

ALUMINUM
CLEAR ANODIZED

FOR 25MM, 32MM, 50MM WIDE BELTS



TYPE - 6F



TYPE - 6



Note : All Dimensions are in MM

10mm PITCH (AT) 25mm WIDE BELTS												
PART NUMBER	NO. OF TEETH	TYPE	DIAMETERS				STOCK BORES		DIMENSIONS		HUB PROJ.	WEIGHT (lbs.)
			P.D.	O.D.	F.D.	HUB	MIN.	MAX.	L	W		
42 AT10/20-2	20	6F	63.66	61.80	67	46	12	16	42	32	10	0.08
42 AT10/22-2	22	6F	70.03	68.15	74	50	12	16	42	32	10	0.11
42 AT10/24-2	24	6F	76.39	74.55	80	58	12	16	42	32	10	0.12
42 AT10/25-2	25	6F	79.58	77.75	82	60	12	16	42	32	10	0.13
42 AT10/27-2	27	6F	85.95	84.10	90	60	12	16	42	32	10	0.15
42 AT10/30-2	30	6F	95.49	93.65	99	60	12	16	42	32	10	0.19
42 AT10/32-2	32	6F	101.86	100.00	105	65	12	16	42	32	10	0.21
42 AT10/36-2	36	6F	114.59	112.75	118	70	16	20	42	32	10	0.26
42 AT10/40-2	40	6F	127.32	125.45	131	80	16	20	42	32	10	0.33
42 AT10/44-2	44	6F	140.05	138.20	144	90	16	20	42	32	10	0.40
42 AT10/48-2	48	6	152.78	150.95	-	95	16	20	42	32	10	0.48
42 AT10/60-2	60	6	190.98	189.10	-	110	16	20	42	32	10	0.76

10mm PITCH (AT) 32mm WIDE BELTS												
PART NUMBER	NO. OF TEETH	TYPE	DIAMETERS				STOCK BORES		DIMENSIONS		HUB PROJ.	WEIGHT (lbs.)
			P.D.	O.D.	F.D.	HUB	MIN.	MAX.	L	W		
50 AT10/20-2	20	6F	63.66	61.80	67	46	12	16	50	40	10	0.08
50 AT10/22-2	22	6F	70.03	68.15	74	50	12	16	50	40	10	0.10
50 AT10/24-2	24	6F	76.39	74.55	80	58	12	16	50	40	10	0.12
50 AT10/25-2	25	6F	79.58	77.75	82	60	12	16	50	40	10	0.13
50 AT10/27-2	27	6F	85.95	84.10	90	60	12	16	50	40	10	0.15
50 AT10/30-2	30	6F	95.49	93.65	99	60	12	16	50	40	10	0.18
50 AT10/32-2	32	6F	101.86	100.00	105	65	12	16	50	40	10	0.21
50 AT10/36-2	36	6F	114.59	112.75	118	70	16	20	50	40	10	0.26
50 AT10/40-2	40	6F	127.32	125.45	131	80	16	20	50	40	10	0.32
50 AT10/44-2	44	6F	140.05	138.20	144	90	16	20	50	40	10	0.41
50 AT10/48-2	48	6	152.78	150.95	-	95	16	20	50	40	10	0.48
50 AT10/60-2	60	6	190.98	189.10	-	110	16	20	50	40	10	0.75

10mm PITCH (AT) 50mm WIDE BELTS												
PART NUMBER	NO. OF TEETH	TYPE	DIAMETERS				STOCK BORES		DIMENSIONS		HUB PROJ.	WEIGHT (lbs.)
			P.D.	O.D.	F.D.	HUB	MIN.	MAX.	L	W		
70 AT10/20-2	20	6F	63.66	61.80	67	46	12	16	70	60	10	0.07
70 AT10/22-2	22	6F	70.03	68.15	74	50	12	16	70	60	10	0.09
70 AT10/24-2	24	6F	76.39	74.55	80	58	12	16	70	60	10	0.11
70 AT10/25-2	25	6F	79.58	77.75	82	60	12	16	70	60	10	0.12
70 AT10/27-2	27	6F	85.95	84.10	90	60	12	16	70	60	10	0.14
70 AT10/30-2	30	6F	95.49	93.65	99	60	12	16	70	60	10	0.18
70 AT10/32-2	32	6F	101.86	100.00	105	65	12	16	70	60	10	0.20
70 AT10/36-2	36	6F	114.59	112.75	118	70	12	16	70	60	10	0.26
70 AT10/40-2	40	6F	127.32	125.45	131	80	12	20	70	60	10	0.33
70 AT10/44-2	44	6F	140.05	138.20	144	90	12	20	70	60	10	0.40
70 AT10/48-2	48	6	152.78	150.95	-	95	16	20	70	60	10	0.47
70 AT10/60-2	60	6	190.98	189.10	-	110	16	20	70	60	10	0.74

Note : Part number listed are for Stock bore.
 Rework services are available to accommodate Max Bore Size
 Drill & Tap Set Screw holes as per request.