HTD® TIMING BELT PULLEY 3MM PITCH (CURVILINEAR TEETH)

ALUMINUM CLEAR ANODIZED

FOR 6MM WIDE BELTS

TYPE - 6

3mm PITCH (HTD) 6mm WIDE BELTS												
OLD PART NUMBER	NEW PART NUMBER	NO. OF TEETH/ GROOVES	TYPE	DIAMETERS				STOCK BORES		DIMENSIONS		WEIGHT (lbs.)
				P.D.	O.D.	F.D.	HUB "C"	MIN.	MAX.	OVERALL LENGTH "L"	FACE WIDTH "W"	
18-3M06-6A	18-3M-06-6A-1/4	18	6	0.677	0.647	-	7/16	1/4	1/4	11/16	25/64	0.01
19-3M06-6A	19-3M-06-6A-1/4	19	6	0.714	0.684	-	15/32	1/4	1/4	11/16	25/64	0.02
20-3M06-6A	20-3M-06-6A-1/4	20	6	0.752	0.722	-	1/2	1/4	5/16	11/16	25/64	0.02
22-3M06-6A	22-3M-06-6A-1/4	22	6	0.827	0.797	-	9/16	1/4	5/16	11/16	25/64	0.02
24-3M06-6A	24-3M-06-6A-1/4	24	6	0.902	0.872	-	5/8	1/4	3/8	11/16	25/64	0.03
25-3M06-6A	25-3M-06-6A-1/4	25	6	0.940	0.910	-	5/8	1/4	3/8	11/16	25/64	0.03
26-3M06-6A	26-3M-06-6A-1/4	26	6	0.977	0.947	-	5/8	1/4	3/8	11/16	25/64	0.03
28-3M06-6A	28-3M-06-6A-1/4	28	6	1.053	1.023	-	45/65	1/4	7/16	11/16	25/64	0.04
30-3M06-6A	30-3M-06-6A-1/4	30	6	1.128	1.098	-	25/32	1/4	7/16	11/16	25/64	0.05
32-3M06-6A	32-3M-06-6A-1/4	32	6	1.203	1.173	-	27/32	1/4	1/2	11/16	25/64	0.05
34-3M06-6A	34-3M-06-6A-1/4	34	6	1.278	1.248	-	59/64	1/4	9/16	23/32	13/32	0.06
36-3M06-6A	36-3M-06-6A-1/4	36	6	1.353	1.323	-	1	1/4	5/8	23/32	13/32	0.07
38-3M06-6A	38-3M-06-6A-1/4	38	6	1.429	1.399	-	1-5/64	1/4	5/8	23/32	13/32	0.08
40-3M06-6A	40-3M-06-6A-1/4	40	6	1.504	1.474	-	1-5/32	1/4	11/16	23/32	13/32	0.10
44-3M06-6A	44-3M-06-6A-1/4	44	6	1.654	1.624	-	1-19/64	1/4	13/16	23/32	13/32	0.12
48-3M06-6A	48-3M-06-6A-5/16	48	6	1.805	1.775	-	1-1/4	5/16	3/4	47/64	13/32	0.13
50-3M06-6A	50-3M-06-6A-5/16	50	6	1.880	1.850	-	1-1/4	5/16	3/4	47/64	13/32	0.14
56-3M06-6A	56-3M-06-6A-5/16	56	6	2.105	2.075	-	1-1/4	5/16	3/4	47/64	13/32	0.17
60-3M06-6A	60-3M-06-6A-5/16	60	6	2.256	2.226	-	1-1/4	5/16	3/4	47/64	13/32	0.19
62-3M06-6A	62-3M-06-6A-5/16	62	6	2.331	2.301	-	1-1/4	5/16	3/4	47/64	13/32	0.20
68-3M06-6A	68-3M-06-6A-5/16	68	6	2.557	2.527	-	1-1/4	5/16	3/4	47/64	13/32	0.23
72-3M06-6A	72-3M-06-6A-5/16	72	6	2.707	2.677	-	1-1/4	5/16	3/4	47/64	13/32	0.26
80-3M06-6A	80-3M-06-6A-5/16	80	6	3.009	2.979	-	1-1/4	5/16	3/4	47/64	13/32	0.31

NOTE : All the pulleys are furnished with two set screw at 90°.
Part Number Mentioned is for Stock bore.
Rework can be done to accommodate maximum bore size.

HTD® TIMING BELT PULLEY 3MM PITCH (CURVILINEAR TEETH)

ALUMINUM CLEAR ANODIZED

FOR 9MM WIDE BELTS

TYPE - 6C

TYPE - 6F

3mm PITCH (HTD) 9mm WIDE BELTS												
OLD PART NUMBER	NEW PART NUMBER	NO. OF TEETH/ GROOVES	TYPE	DIAMETERS				STOCK BORES		DIMENSIONS		WEIGHT (lbs.)
				P.D.	O.D.	F.D.	HUB "C"	MIN.	MAX.	OVERALL LENGTH "L"	FACE WIDTH "W"	
10-3M09-6CA	10-3M-09-6CA-1/8	10	6C	0.376	0.346	1/2	1/2	1/8	-	11/16	-	0.01
11-3M09-6CA	11-3M-09-6CA-1/8	11	6C	0.414	0.384	17/32	17/32	1/8	-	11/16	-	0.01
12-3M09-6CA	12-3M-09-6CA-3/16	12	6C	0.451	0.421	37/64	37/64	3/16	-	11/16	-	0.02
13-3M09-6CA	13-3M-09-6CA-3/16	13	6C	0.489	0.459	39/64	39/64	3/16	-	11/16	-	0.02
14-3M09-6CA	14-3M-09-6CA-3/16	14	6C	0.526	0.496	41/64	41/64	3/16	-	11/16	-	0.02
15-3M09-6CA	15-3M-09-6CA-3/16	15	6C	0.564	0.534	11/16	11/16	3/16	-	11/16	-	0.02
16-3M09-6CA	16-3M-09-6CA-3/16	16	6C	0.602	0.572	45/64	45/64	3/16	-	11/16	-	0.02
17-3M09-6CA	17-3M-09-6CA-3/16	17	6C	0.639	0.609	47/64	47/64	3/16	-	11/16	-	0.03
18-3M09-6FA	18-3M-09-6FA-1/4	18	6F	0.677	0.647	51/64	7/16	1/4	1/4	13/16	1/2	0.02
19-3M09-6CA	19-3M-09-6CA-1/4	19	6C	0.714	0.684	13/16	15/32	1/4	-	13/16	1/2	0.02
20-3M09-6FA	20-3M-09-6FA-1/4	20	6F	0.752	0.722	57/64	1/2	1/4	5/16	13/16	1/2	0.02
22-3M09-6FA	22-3M-09-6FA-1/4	22	6F	0.827	0.797	15/16	9/16	1/4	5/16	13/16	1/2	0.03
24-3M09-6FA	24-3M-09-6FA-1/4	24	6F	0.902	0.872	1-1/32	5/8	1/4	3/8	13/16	1/2	0.04
25-3M09-6FA	25-3M-09-6FA-1/4	25	6F	0.940	0.910	1-1/16	5/8	1/4	3/8	13/16	1/2	0.04
26-3M09-6FA	26-3M-09-6FA-1/4	26	6F	0.977	0.947	1-17/64	5/8	1/4	3/8	13/16	1/2	0.04
28-3M09-6FA	28-3M-09-6FA-1/4	28	6F	1.053	1.023	1-11/64	45/64	1/4	7/16	13/16	1/2	0.05
30-3M09-6FA	30-3M-09-6FA-1/4	30	6F	1.128	1.098	1-1/4	25/32	1/4	7/16	13/16	1/2	0.06
32-3M09-6FA	32-3M-09-6FA-1/4	32	6F	1.203	1.173	1-21/64	27/32	1/4	1/2	13/16	1/2	0.07
34-3M09-6FA	34-3M-09-6FA-1/4	34	6F	1.278	1.248	1-21/64	59/64	1/4	9/16	27/32	17/32	0.08
36-3M09-6FA	36-3M-09-6FA-1/4	36	6F	1.353	1.323	1-15/32	1	1/4	5/8	27/32	17/32	0.09
38-3M09-6FA	38-3M-09-6FA-1/4	38	6F	1.429	1.399	1-35/64	1-5/64	1/4	5/8	27/32	17/32	0.10
40-3M09-6FA	40-3M-09-6FA-1/4	40	6F	1.504	1.474	1-5/8	1-5/32	1/4	11/16	27/32	17/32	0.11
44-3M09-6FA	44-3M-09-6FA-1/4	44	6F	1.654	1.624	1-25/32	1-19/64	1/4	13/16	27/32	17/32	0.14

NOTE : Pulleys with 10 to 13 grooves have 1set screw; others have 2 at 90°.

Part Number Mentioned is for Stock bore.

Rework can be done to accommodate maximum bore size.

HTD® TIMING BELT PULLEY 3MM PITCH (CURVILINEAR TEETH)

ALUMINUM CLEAR ANODIZED

FOR 9MM WIDE BELTS

TYPE - 6

3mm PITCH (HTD) 9mm WIDE BELTS												
OLD PART NUMBER	NEW PART NUMBER	NO. OF TEETH/ GROOVES	TYPE	DIAMETERS				STOCK BORES		DIMENSIONS		WEIGHT (lbs.)
				P.D.	O.D.	F.D.	HUB "C"	MIN.	MAX.	OVERALL LENGTH "L"	FACE WIDTH "W"	
18-3M09-6A	18-3M-09-6A-1/4	18	6	0.677	0.647	-	7/16	1/4	1/4	13/16	1/2	0.02
19-3M09-6A	19-3M-09-6A-1/4	19	6	0.714	0.684	-	15/32	1/4	1/4	13/16	1/2	0.02
20-3M09-6A	20-3M-09-6A-1/4	20	6	0.752	0.722	-	1/2	1/4	5/16	13/16	1/2	0.02
22-3M09-6A	22-3M-09-6A-1/4	22	6	0.827	0.797	-	9/16	1/4	5/16	13/16	1/2	0.03
24-3M09-6A	24-3M-09-6A-1/4	24	6	0.902	0.872	-	5/8	1/4	3/8	13/16	1/2	0.03
25-3M09-6A	25-3M-09-6A-1/4	25	6	0.940	0.910	-	5/8	1/4	3/8	13/16	1/2	0.04
26-3M09-6A	26-3M-09-6A-1/4	26	6	0.977	0.947	-	5/8	1/4	3/8	13/16	1/2	0.04
28-3M09-6A	28-3M-09-6A-1/4	28	6	1.053	1.023	-	45/64	1/4	7/16	13/16	1/2	0.05
30-3M09-6A	30-3M-09-6A-1/4	30	6	1.128	1.098	-	29/32	1/4	7/16	13/16	1/2	0.06
32-3M09-6A	32-3M-09-6A-1/4	32	6	1.203	1.173	-	27/32	1/4	1/2	13/16	1/2	0.07
34-3M09-6A	34-3M-09-6A-1/4	34	6	1.278	1.248	-	59/64	1/4	9/16	27/32	17/32	0.08
36-3M09-6A	36-3M-09-6A-1/4	36	6	1.353	1.323	-	1	1/4	5/8	27/32	17/32	0.09
38-3M09-6A	38-3M-09-6A-1/4	38	6	1.429	1.399	-	1-5/64	1/4	5/8	27/32	17/32	0.10
40-3M09-6A	40-3M-09-6A-1/4	40	6	1.504	1.474	-	1-5/32	1/4	11/16	27/32	17/32	0.12
44-3M09-6A	44-3M-09-6A-1/4	44	6	1.654	1.624	-	1-19/64	1/4	13/16	27/32	17/32	0.14
45-3M09-6A	45-3M-09-6A-1/4	45	6	1.692	1.662	-	1-19/64	1/4	13/16	27/32	17/32	0.15
48-3M09-6A	48-3M-09-6A-5/16	48	6	1.805	1.775	-	1-1/4	5/16	3/4	7/8	1/2	0.16
50-3M09-6A	50-3M-09-6A-5/16	50	6	1.880	1.850	-	1-1/4	5/16	3/4	7/8	1/2	0.17
56-3M09-6A	56-3M-09-6A-5/16	56	6	2.105	2.075	-	1-1/4	5/16	3/4	7/8	1/2	0.20
60-3M09-6A	60-3M-09-6A-5/16	60	6	2.256	2.226	-	1-1/4	5/16	3/4	7/8	1/2	0.23
62-3M09-6A	62-3M-09-6A-5/16	62	6	2.331	2.301	-	1-1/4	5/16	3/4	7/8	1/2	0.24
68-3M09-6A	68-3M-09-6A-5/16	68	6	2.56	2.527	-	1-1/4	5/16	3/4	7/8	1/2	0.28
72-3M09-6A	72-3M-09-6A-5/16	72	6	2.707	2.677	-	1-1/4	5/16	3/4	7/8	1/2	0.31
80-3M09-6A	80-3M-09-6A-5/16	80	6	3.01	2.979	-	1-1/4	5/16	3/4	7/8	1/2	0.38

NOTE : All the pulleys are furnished with two set screw at 90°.
Part Number Mentioned is for Stock bore.
Rework can be done to accommodate maximum bore size.